



**The highest  
quality ALD  
systems for  
demanding  
applications.**

## **PICOSUN® R-200 STANDARD**

**The PICOSUN® R-200 Standard ALD systems are suitable for R&D on dozens of applications such as IC components, MEMS devices, displays, LEDs, lasers, and 3D objects such as lenses, optics, jewelry, coins, and medical implants.**

The PICOSUN® R-200 Standard ALD system is the market leader in thermal ALD research tools. It has become the tool of choice both for companies and research institutes driven by innovation.

The agile design enables the highest quality ALD film depositions together with the ultimate flexibility of the system to fit future needs and applications. The patented hot-wall design with fully separate inlets and instrumentation enables particle-free processing adaptable on a wide range of materials on wafers, 3D objects, and all nanoscale features. Excellent uniformity even on the most challenging through-porous, ultra-high aspect ratio, and nanoparticle samples can be achieved thanks to our proprietary Picoflow™ technology. The PICOSUN® R-200 Standard systems are equipped with highly functional and easily exchangeable precursor sources for liquid, gaseous, and solid chemicals. Integration with glove boxes, powder chambers, and various in situ analytics systems enable efficient and flexible research with good results, no matter what your research area is now, or what it might become later on.

### **TECHNICAL FEATURES**

#### **Typical substrate size and type**

- 50-200 mm single wafers
- 156 mm x 156 mm solar Si wafers
- 3D objects
- Powders and particles
- Mini-batch
- Porous, through-porous, and high aspect ratio (up to 1:2500)

#### **Processing temperature**

- 50 – 500°C

#### **Typical processes**

- $\text{Al}_2\text{O}_3$ ,  $\text{TiO}_2$ ,  $\text{SiO}_2$ ,  $\text{Ta}_2\text{O}_5$ ,  $\text{HfO}_2$ ,  $\text{ZnO}$ ,  $\text{ZrO}_2$ ,  $\text{TiN}$ ,  $\text{AlN}$ , metals such as Pt or Ir

#### **Substrate loading**


- Manual loading with a pneumatic lift
- Load lock with magnetic manipulator arm

#### **Precursors**


- Liquid, solid, gas, ozone
- Up to 6 sources with 4 separate inlets

#### **Options**

- Picoflow™ diffusion enhancer, RGA,  $\text{N}_2$  generator, gas scrubber, customized designs, glove box compatibility for inert loading




## THE PRINCIPLE OF ALD



Introduction of molecules  
containing element A.



Adsorption of the molecules  
on the surface.



Introduction of molecules  
containing element B and  
reaction with element A on the  
surface.



Completion of one monolayer  
of compound AB.

Repeat cycle till desired film  
thickness is reached.

SiSTEM Technology Limited  
Grafton Suite  
Caswell Science & Technology Park  
Towcester  
Northamptonshire  
NN12 8EQ  
United Kingdom

Email:  
[sales@sistemtechnology.com](mailto:sales@sistemtechnology.com)

Telephone:  
+44 1327 317621



**pic**  **sun**

This technology is protected via  
granted patents or is the subject of  
pending patent applications.

PICOSUN® R-200 Standard • Version 09\_2021